


# ChargePoint CP4300 Top CMK sign template



CP4300  
Pedestal  
with CMK



CP4300  
Wall Mount  
with CMK



## NOTES & REQUIREMENTS


- Artwork must be in **vector** format. Do not use raster images.
- Artwork must be in CMYK process color. (Call out any PMS numbers for reference, but artwork is screen printed using CMYK only.)
- Solid color only, no transparency or gradients
- For full bleed artwork, provide minimum 5-mm bleed
- Convert all fonts to outlines

## MATERIALS


- Total thickness 0.040" max: White styrene, 0.03" thick; Reflective material 3M 5100-10 white; External laminate 0.002" thick ORAGUARD 290 PVC (for UV protection).
- NOR-COTE XL6 ink over reflective material
- Finished label is ROHS compliant

ChargePoint standard artwork is included for reference only.

Place custom artwork on CUSTOMER ARTWORK layer:



# ChargePoint CP4100 and CP4300 Pedestal and bottom CMK sign template



70mm to top edge  
Inactive area.  
This area is hidden  
by the head unit.

70 mm

### NOTES & REQUIREMENTS


- Artwork must be in **vector** format. Do not use raster images.
- Artwork must be in CMYK process color. (Call out any PMS numbers for reference, but artwork is screen printed using CMYK only.)
- Solid color only, no transparency or gradients
- For full bleed artwork, provide minimum 5-mm bleed
- Convert all fonts to outlines

### MATERIALS

- Total thickness 0.040" max:  
White styrene, 0.03" thick;  
Reflective material 3M 5100-10 white;  
External laminate 0.002" thick ORAGUARD 290 PVC (for UV protection).
- NOR-COTE XL6 ink over reflective material
- Finished label is ROHS compliant

ChargePoint standard artwork is included for reference only.

Place custom artwork on CUSTOMER ARTWORK layer:



3M 5100-10 Reflective material  
WHITE

MATCH PMS 158C

848.3 ± 1 mm  
[33.4"]

Trim

Bleed

Bottom Edge

101.5 ± 0.5 mm  
[4.00"]